

McGUIRE

A Division of Systems, Inc.

VSH SERIES

INTERNATIONAL
DOOR

VERTICAL STORING HYDRAULIC LEVELER



* VSH Series, 6' x 5', 40,000 CIR, with remote motor shown

- ▶ Easy push button operation for smooth, consistent operation with a hydraulic system that provides for full float at all positions
- ▶ Power-up and power-down control panel with constant pressure push buttons for safety
- ▶ Below dock end load capability
- ▶ Dual maintenance struts included for added safety
- ▶ Structural "C" & "I" Beam Deck Supports
- ▶ Mechanical locking mechanism with push button release for added safety
- ▶ 3" high safety run-off guards are included on platform
- ▶ Rear embed channel included with each VSH has factory installed hinges for ease of installation

GENERAL DESCRIPTION: All McGuire VSH Series dock levelers incorporate the use of hydraulics to raise and lower both the platform and lip. A single push button activates a hydraulic pump for operating both lip and hoist cylinders. Systems, Inc. is an active member of Loading Dock Equipment Manufacturers (LODEM), a product section of the Material Handling Industry. Unit conforms to OSHA, U.S. Department of Commerce Standard CS-202-56 and is manufactured in compliance with the American National Standard of Safety Performance and Testing of Dock Leveling Devices (ANSI) MH 30.1. Unit is manufactured by McGuire.

OPERATION: The VSH Series Lever is controlled remotely from a multiple push button control pane that includes raise, lower and lip control buttons. Lip control button allows independent extension and retraction of the lip. Power-up and power-down requires constant pressure on controls or unit stops in place for added safety. Service range of 10" above to 8" below dock level is standard on all units. 3" run off guards are provided each side of platform as standard. Dual maintenance struts are standard. Factory finish includes rust inhibitive prime coat industrial grade finish. Special coating and colors are optional.

CONSTRUCTION: The platform is constructed of 1/4" thick 4-way high tensile 50,000 minimum yield A572 safety tread plate. Platforms are reinforced and supported by full length structural "C" channels and wide flanged "I" beams sized properly for 40,000, 45,000 and 50,000 lbs Comparative Industry Rating (CIR) units --welded to deck and front and rear headers for firm structural support. Front and rear header plates are 1/2" thick, hot rolled steel. VSH series lips are 4-way safety tread plate. The 40,000 CIR is 5/8" thick, the 45,000 and 50,000 CIR are 3/4" thick. The standard lip length is 16" with 18" and 20" available. Hinge tubes are 1 7/8" OD x 3/8" wall or 2 1/8" OD x 1/2" wall depending on CIR. All lip hinge pins are 1" diameter M1044 steel. All units have grease fittings as standard. All platforms are designed to compensate for up to 4" of canted trailer bed.

HYDRAULICS: Platform is raised by a main hydraulic cylinder; all hydraulic hoses are routed under the leveler platform, away from debris. Hoist cylinder is a hard chrome-plated design with a 3 1/2" ID bore and anti-corrosive rod coating. Main cylinder is equipped with a flow control valve to meter the decent of the ramp. Lip operation is controlled by a hard chrome plated cylinder having a 2 1/2" ID bore. Motor pump is deck mounted or remote mounted for easy access.

SAFETY EQUIPMENT: 3" high run off guards are included on either side of platform. Dual maintenance struts on sides of platform for added safety are released via push button. Raise and lower push buttons are constant pressure type and unit halts in place if button is released. The VSH leveler locks in the stored position mechanically and hydraulically. The mechanical lock is automatically released by the lower button.

COLORS: Levelers painted slate blue. Other colors available. Consult factory.

DOCK BUMPERS: Two B412-14 laminated 4 1/2" thick x 12" high x 14" wide bumpers are included. Two VB420-11F vertical laminated 4 1/2" thick x 20" high x 11" wide with bumper bracket assembly are recommended. Optional sizes and types are available.

VEHICLE RESTRAINT SYSTEMS: McGuire VSH Series vertical storing hydraulic levelers can be equipped with STOP-TITE®, TPR™ or a HOLD-TITE® series vehicle restraint or a Light Communication System to help prevent unexpected trailer departure from the loading dock and minimize trailer creep during the loading/unloading process and to enhance communication at the dock area.

ELECTRICAL: Hydraulic pump motor either 1 1/2 HP TENV at 120v or 208v, single phase or at 208v, 230v, 460v, or 575v three phase. Electrical control panel is Nema 12 enclosure. All electrical components, connections and wiring are UL listed or recognized. Please Note: Unless specifically noted on quotation, all electrical requirements are the responsibility of others.

WARRANTY: All McGuire VSH Series models feature a full one (1) year base warranty on all structural, hydraulic and electrical parts, including freight and labor charges in accordance with McGuire's Standard Warranty Policy. Structural and hydraulic components carry an additional full four (4) year extended warranty with parts and labor. McGuire warrants all components to be free of defects in materials and workmanship, under normal use, during the warranty period. This base warranty period begins upon the completion of installation or the sixtieth (60th) day after shipment, whichever is earlier. Additional warranty extensions may be available upon approved submittal of application information.

DOCK LEVELER



A Division of Systems, Inc.

VSH SERIES

VERTICAL STORING HYDRAULIC LEVELER

Optional Equipment for VSH Series Vertical Storing Hydraulic Dock Leveler

Check Options Desired

- | | |
|--|---|
| <input type="checkbox"/> Grease Fittings | <input type="checkbox"/> Vertical Bumpers (laminated) |
| <input type="checkbox"/> Lip Keepers | <input type="checkbox"/> VB420-11 <input type="checkbox"/> VB424-11 |
| <input type="checkbox"/> 18" Lip | <input type="checkbox"/> 6" Thick Dock Bumpers |
| <input type="checkbox"/> 20" Lip | <input type="checkbox"/> Steel Faced Dock Bumpers |
| <input type="checkbox"/> Integrated Controls | <input type="checkbox"/> HOLD-TITE® restraint |
| <input type="checkbox"/> Leveler Stored Indicator Light | <input type="checkbox"/> TPR™ restraint |
| <input type="checkbox"/> Deck Mounted Motor | <input type="checkbox"/> STOP-TITE® restraint (automatic) |
| <input type="checkbox"/> Remote Mounted Motor | <input type="checkbox"/> Light Communication System |
| <input type="checkbox"/> Hoist Cylinder Embed Plate | <input type="checkbox"/> Wheel Chocks Model# _____ |
| <input type="checkbox"/> Gusseted Bumper Brackets with Load Distribution Plate | <input type="checkbox"/> Dock Light (no bulb) Model# _____ |
| | <input type="checkbox"/> Other _____ |
| | <input type="checkbox"/> Other _____ |

Dimensions and Capacities

Select a Model and a Capacity

MODEL - NOMINAL SIZE

COMPARATIVE INDUSTRY RATING (CIR)

- | | | | |
|----------------------------------|-----------|----------------------------------|-----------|
| <input type="checkbox"/> VSH-65 | 6' x 5' | <input type="checkbox"/> VSH-658 | 6'6" x 8' |
| <input type="checkbox"/> VSH-66 | 6' x 6' | <input type="checkbox"/> VSH-75 | 7' x 5' |
| <input type="checkbox"/> VSH-68 | 6' x 8' | <input type="checkbox"/> VSH-76 | 7' x 6' |
| <input type="checkbox"/> VSH-655 | 6'6" x 5' | <input type="checkbox"/> VSH-78 | 7' x 8' |
| <input type="checkbox"/> VSH-656 | 6'6" x 6' | | |

- 40,000 LBS.
- 45,000 LBS.
- 50,000 LBS.

Customer: _____

Job: _____

Location: _____

Number of Units: _____

Model: _____

Voltage/Phase: _____

Represented By: _____

Sales Rep: _____

Certified for Construction:

By: _____

Title: _____

Date: _____

Company: _____

City: _____

State: _____

Consistent with our policy of continuing product improvement, we reserve the right to change product specifications without notice or obligation.

McGuire • Division of Systems, Inc. • W194 N11481 McCormick Dr. • P.O. Box 309 • Germantown, WI 53022

Phone: 800.624.8473 • Fax: 262.255.4199 • www.DockSystemsInc.com

DOCK LEVELER

SS VSH 09/12